


## HCSF SERIES

High Performance Flexible Figure 8 Twin Audio Cable 50V 90°C



### APPLICATIONS:

**Audio** Super flexible oxygen free copper and figure 8 construction for speakers and audio controls.

### PRODUCT FEATURES:

- ▶ Very fine stranded copper conductor
- ▶ Extra high flexibility
- ▶ Trace line for easy identification during installation
- ▶ Provides easy separation at each end
- ▶ UV stabilised
- ▶ Flame retardant
- ▶ Heat, oil and chemical resistant (See *Technical Section*)

### CONSTRUCTION:

**Conductor** Annealed plain copper stranded extreme flexibility (Class 5 & 6).

**Insulation** Special SPVC V-75.

### CHARACTERISTICS:

**Operating Temperature Range** Fixed -20°C to 70°C / Flexing -5°C to 70°C.

**Maximum Conductor Temperature** 75°C.

**Rated Voltage** 50VRMS/150VDC.

**Minimum Bending Radius** Fixed 10 x cable height / Flexing 15 x cable height.

**Sheath Colour** Clear c/w one stripe.

**Relevant Standards** AS/NZS 1125, IEC 60332-1,

**RoHS** Compliant.

Code	No. of Cores x Size  (mm <sup>2</sup> )	Nearest AWG	Approx. Stranding  No. of wires x mm <sup>2</sup>	Approx. Overall Diameter  (mm)	Approx. Weight  (Kg/Km)	Maximum Resistance  ohms/Km 20°C
<b>HCSF3319</b>	2 x 2.0	14	80/0.18	7.0 x 3.5	58	8.45