

# GALVANISED FLEXIBLE CONDUIT & FITTINGS

## GFC SERIES

Flexible Metal Conduit  
Galvanised Steel Bare IP40



### APPLICATIONS:

For use in connecting machinery in processing plants and areas subject to sparks, heat and environments where external hazards may cause damage to cables.

### PRODUCT FEATURES:

- ▶ High mechanical strength
- ▶ Halogen free
- ▶ Low fire hazard

### CONSTRUCTION:

Highly flexible helically wound galvanised steel.

### CHARACTERISTICS:

**Operating Temperature Range** -40°C to 300°C.  
**Protection Class** IP40.

Code	Colour	OD (Approx) (mm)	ID (Approx) (mm)	Minimum Bending Radius (mm)	Role Length (m)	Minimum Quantity Length (m)
<b>GFC16</b>	Galvanised	20	16	40	50	1
<b>GFC20</b>	Galvanised	24	20	45	50	1
<b>GFC25</b>	Galvanised	30	25	55	50	1
<b>GFC32</b>	Galvanised	37	32	70	25	1
<b>GFC40</b>	Galvanised	45	40	80	25	1

**NOTE: SEE PAGE 256 FOR STRAIGHT AND 90° ANGLED CONNECTORS FOR FLEXIBLE CONDUIT.**