

GFCLT SERIES

Liquid Tight Flexible Metal Conduit
Galvanised Steel PVC Coated IP68



APPLICATIONS:

For use in connecting machinery in processing plants and areas subject to sparks, heat and environments where external hazards may cause damage to cables. The PVC coating offers an IP68 rating when used in conjunction with our galvanised flexi-conduit connectors.

PRODUCT FEATURES:

- ▶ High mechanical strength
- ▶ Superior oil, grease and weather resistance
- ▶ UV stabilised

CONSTRUCTION:

Highly flexible helically wound galvanised steel coated with liquid tight PVC for higher IP rating.

CHARACTERISTICS:

Operating Temperature Range -20°C to 50°C.
Protection Class IP68.

Code	Colour	OD (Approx) (mm)	ID (Approx) (mm)	Minimum Bending Radius (mm)	Role Length (m)	Minimum Quantity Length (m)
GFCLT16	Black	20.4	15.6	120	50	1
GFCLT20	Black	24.4	19.6	150	50	1
GFCLT25	Black	31.0	24.5	180	50	1
GFCLT32	Black	39.0	31.5	250	25	1
GFCLT40	Black	47.0	40.0	300	25	1

NOTE: SEE PAGE 256 FOR STRAIGHT AND 90° ANGLED CONNECTORS FOR FLEXIBLE CONDUIT.