

CONDUIT, FITTINGS & SADDLES

GFCP SERIES

Flexible Metal Conduit
Galvanised Steel PVC Coated IP65



APPLICATIONS:

For use in connecting machinery in processing plants and areas subject to sparks, heat and environments where external hazards may cause damage to cables. The PVC coating offers an IP65 rating when used in conjunction with our galvanised flexi-conduit connectors.

PRODUCT FEATURES:

- ▶ High mechanical strength
- ▶ Superior oil, grease and weather resistant
- ▶ UV stabilised

CONSTRUCTION:

Highly flexible helically wound galvanised steel coated with PVC for higher IP rating.

CHARACTERISTICS:

Operating Temperature Range -20°C to 50°C.
Protection Class IP65.

Code	Colour	OD (Approx) (mm)	ID (Approx) (mm)	Minimum Bending Radius (mm)	Role Length (m)	Minimum Quantity Length (m)
GFCP16	Black	20	16	40	50	1
GFCP20	Black	24	20	45	50	1
GFCP25	Black	30	25	55	50	1
GFCP32	Black	37	32	70	25	1
GFCP40	Black	45	40	80	25	1

NOTE: SEE PAGE 256 FOR STRAIGHT AND 90° ANGLED CONNECTORS FOR FLEXIBLE CONDUIT.