

## GLANDS & ACCESSORIES

### GMF SERIES

**Metal IP54 Gland for Flat Flexible Cables  
(less Locknut)**



#### APPLICATIONS:

**Glanding** For glanding of FLAT flexible cables.

#### PRODUCT FEATURES:

- ▶ Halogen free
- ▶ Silicone free
- ▶ Phosphorous free
- ▶ Cadmium free
- ▶ Self extinguishing

#### CONSTRUCTION:

**Material** Bright nickel plated extruded brass gland body and compression head.

**Seal** Oil resistant rubber.

**Pressure Plate** Galvanised steel.

#### CHARACTERISTICS:

**Operating Temperature Range** -40°C to 80°C. Up to 100°C for short periods.

**Protection Class** Water rating IP54.

Code	Entry Thread PG	Thread Length (mm)	Cable Size Min - Max (mm)	Hexagonal Across Flats (mm)	Hexagonal Circumference (mm)	Assembled Length (mm)
<b>GMF020611-20x16</b>	M20 x 1.5	6.0	4.0 - 5.5 x 13.0 - 15.0	22	24	19.5
<b>GMF020611-25x16</b>	M25 x 1.5	7.0	4.0 - 5.5 x 13.0 - 15.0	22	30	19.5
<b>GMF020611-25x21</b>	M25 x 1.5	7.0	4.5 - 7.5 x 14.0 - 20.0	28	30	23.0
<b>GMF020611-32x29</b>	M32 x 1.5	8.0	4.5 - 10.0 x 19.0 - 27.0	37	40	25.5
<b>GMF020611-40x29</b>	M40 x 1.5	8.0	4.5 - 10.0 x 19.0 - 27.0	37	43	25.5
<b>GMF020611-40x36</b>	M40 x 1.5	8.0	4.5 - 13.0 x 29.0 - 36.0	47	50	29.5
<b>GMF020611-50x36</b>	M50 x 1.5	9.0	4.5 - 13.0 x 29.0 - 36.0	47	55	29.5
<b>GMF020611-50x42</b>	M50 x 1.5	9.0	4.5 - 14.0 x 38.0 - 44.0	54	57	33.0
<b>GMF020611-63x48</b>	M63 x 1.5	10.0	5.0 - 18.0 x 44.0 - 53.0	60	66	35.0
<b>CURVED CABLE ENTRY</b>						
<b>GMF020616-63x48</b>	M63 x 1.5	10.0	6.0 - 9.0 x 54.0 - 62.0	60	66	35.0