

## GWPMEX/GWPEX SERIES

Surefit Explosive Atmosphere  
Unarmoured Extended Table Cable  
Glands IP66 (less locknut)



### APPLICATIONS:

**Glanding** For glanding circular unarmoured cables.

### PRODUCT FEATURES:

- ▶ Explosion proof
- ▶ Weatherproof

### OPTIONAL ACCESSORIES:

- ▶ PVC shroud
- ▶ Earth tag
- ▶ Adaptors and reducers



### CONSTRUCTION:

**Material** Bright nickel plated extruded brass gland body, serving seal, skid washer and back nut (also available in stainless steel).

**Seal** Rubber.

**O-Ring** Rubber.

### CHARACTERISTICS:

**Operating Temperature Range** -20°C to +80°C (up to 100 °C for short periods).



**Protection Class** IP66.

**Relevant Standards** AS/NZS2380.1-1989, AS/NZS2380.2-1991, AS/NZS1939-1990

**Area Classification** Class 1, Zone 1, Group 1 & IIC, Class II.

**Apparatus Group** Exd, Exe, Exp DIP.

**Certificate of Conformity** ANZEx 07.3024.



Code	Cable Size A (mm)		Entry Thread x Pitch B (mm)	Across Corners	Across Flats C (mm)	Maximum Protrusion D (mm)	Thread Length E (mm)	Tail Length F (mm)	Tail Diameter G (mm)
	Min	Max							
GWPMEX0	3.2	7.1	M20x1.5	25.9	22.3	49.3	13	16.7	15.9
GWPMEX1	6.6	9.5	M20x1.5	25.9	22.3	49.3	13	16.7	15.9
GWPMEX1A	9.0	11.9	M20x1.5	29.7	25.6	49.6	13	16.7	15.9
GWPMEX1B-25	11.4	14.3	M25x1.5	33.1	28.5	53.6	15	20.7	19.1
GWPMEX2	13.8	17.5	M25x1.5	36.1	33.3	63.4	15	27.2	25.4
GWPMEX2A-32	16.9	20.1	M32x1.5	40.4	37.2	64.8	21	27.2	25.4
GWPMEX3	19.6	23.8	M32x1.5	48.2	44.4	73.7	21	33.7	31.8
GWPMEX3A	23.0	27.0	M32x1.5	48.2	44.4	73.7	21	33.7	31.8
GWPMEX4	25.4	29.4	M40x1.5	61.3	56.5	81.5	21	41.5	38.1
GWPMEX4A	28.6	32.5	M40x1.5	61.3	56.5	81.5	21	41.5	38.1
GWPMEX5	31.5	36.5	M50x1.5	73.9	68.2	98.0	21	54.7	50.8
GWPMEX5A	35.5	40.5	M50x1.5	73.9	68.2	98.0	21	54.7	50.8
GWPMEX5B	39.5	43.8	M50x1.5	73.9	68.2	98.0	21	54.7	50.8
GWPMEX6	42.8	48.4	M63x1.5	87.7	80.9	113.6	22	70.2	63.5
GWPMEX6A	47.4	52.4	M63x1.5	87.7	80.9	113.6	22	70.2	63.5
GWPMEX6B	51.4	56.0	M63x1.5	87.7	80.9	113.6	22	70.2	63.5
GWPEX7A	55.0	59.3	2.5" BSP	99.7	92.0	134.8	24	91.4	76.2
GWPEX7B	58.1	62.6	2.5" BSP	99.7	92.0	134.8	24	91.4	76.2
GWPEX7C	61.4	65.9	2.5" BSP	99.7	92.0	134.8	24	91.4	91.4

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.