

# GLANDS & ACCESSORIES

## GWPM/GWP SERIES

Surefit Explosive Atmosphere  
Unarmoured Cable Glands  
IP66 (less locknut)



### APPLICATIONS:

**Glanding** For glanding circular unarmoured cables.

### PRODUCT FEATURES:

- ▶ Explosion proof
- ▶ Weatherproof
- ▶ Dust excluding ignition proof

### OPTIONAL ACCESSORIES:

- ▶ PVC shroud
- ▶ Earth tag
- ▶ Adaptors and reducers



### CONSTRUCTION:

**Material** Bright nickel plated extruded brass gland body, serving seal, skid washer and back nut (also available in stainless steel).

**Seal** Rubber.

**O-Ring** Rubber.

### CHARACTERISTICS:

**Operating Temperature Range** -20°C to +80°C. (Up to 100°C for short periods).

**Protection Class** IP66.


**Relevant Standards** AS/NZS2380.1-1989, AS/NZS2380.2-1991, AS/NZS1939-1990.

**Area Classification** Class 1, Zone 1, Group 1 & IIC, Class II.

**Apparatus Group** Exd, Exe, Exp DIP.

**Certificate of Conformity** ANZEx 07.3024.

See over for full product table ▶



## GWPM/GWP SERIES continued

Code	Cable Size A (mm)		Entry Thread x Pitch B (mm)	Across Flats		Maximum Protrusion D (mm)	Thread Length E (mm)
	Min	Max		C (mm)			
<b>GWPM0</b>	3.2	7.1	M20x1.5	22.3		29.5	13
<b>GWPM1</b>	6.6	9.5	M20x1.5	22.3		29.5	13
<b>GWPM1A</b>	9.0	11.9	M20x1.5	25.6		29.8	13
<b>GWPM1B-25</b>	11.4	14.3	M25x1.5	28.5		29.8	15
<b>GWPM2</b>	13.8	17.5	M25x1.5	33.3		31.7	15
<b>GWPM2A-32</b>	16.9	20.1	M32x1.5	37.2		33.1	21
<b>GWPM3</b>	19.3	23.8	M32x1.5	44.4		34.0	21
<b>GWPM3A</b>	23.0	27.0	M32x1.5	44.4		34.0	21
<b>GWPM4</b>	25.4	29.4	M40x1.5	56.5		34.0	21
<b>GWPM4A</b>	28.6	32.5	M40x1.5	56.5		34.0	21
<b>GWPM5</b>	31.5	36.5	M50x1.5	68.2		36.2	21
<b>GWPM5A</b>	35.5	40.5	M50x1.5	68.2		36.2	21
<b>GWPM5B</b>	39.5	43.8	M50x1.5	68.2		36.2	21
<b>GWPM6</b>	42.8	48.4	M63x1.5	80.9		37.5	22
<b>GWPM6A</b>	47.4	52.4	M63x1.5	80.9		37.5	22
<b>GWPM6B</b>	51.4	56.0	M63x1.5	80.9		37.5	22
<b>GWP7A</b>	55.0	59.3	2.5" BSP	92.0		40.5	24
<b>GWP7B</b>	58.1	62.6	2.5" BSP	92.0		40.5	24
<b>GWP7C</b>	61.4	65.9	2.5" BSP	92.0		40.5	24
<b>GWP8A</b>	64.5	69.1	3.0" BSP	104.0		40.8	24
<b>GWP8B</b>	67.7	72.3	3.0" BSP	104.0		40.8	24
<b>GWP8C</b>	70.9	75.5	3.0" BSP	104.0		40.8	24
<b>GWP8D</b>	74.1	78.6	3.0" BSP	104.0		40.8	24
<b>GWP9A</b>	77.0	81.8	3.5" BSP	117.5		40.8	24
<b>GWP9B</b>	80.2	85.0	3.5" BSP	117.5		40.8	24
<b>GWP9C</b>	83.4	88.2	3.5" BSP	117.5		40.8	24
<b>GWP9D</b>	86.6	91.2	3.5" BSP	117.5		40.8	24
<b>GWP10A</b>	89.7	94.5	4.0" BSP	133.0		40.8	24
<b>GWP10B</b>	92.2	97.7	4.0" BSP	133.0		40.8	24
<b>GWP10C</b>	96.1	100.9	4.0" BSP	133.0		40.8	24
<b>GWP10D</b>	99.3	103.9	4.0" BSP	133.0		40.8	24