

FLEXIBLE MULTI CORE CABLES

SMC SERIES

Flexible Industrial Copper Braid Screen Cable 0.6/1KV 90°C



APPLICATIONS:

Power Suitable for indoor/outdoor power supplies and industrial applications.

Safety Copper braid for earth connection and screening purposes.

Leads Suitable for dry and damp industrial applications

PRODUCT FEATURES:

- ▶ Yellow sheath for high visibility
- ▶ Tear, notch, pressure and water resistance
- ▶ UV stabilised
- ▶ Flame retardant
- ▶ Resistant to environmental factors like oxidation, ozone and sunlight
- ▶ Heat, oil and chemical resistant (*See Technical Section*)

CONSTRUCTION:

Conductor Annealed fine wires of plain electrolytic copper stranded for HIGH flexibility VDE 0295 (Class 5).

Insulation V-90HT.

Inner Sheath SER V-90HT.

Screening Flexible copper braid.

Sheath SER V-90HT.

CHARACTERISTICS:

Operating Temperature Range Fixed -20°C to 90°C / Flexing -5°C to 90°C.

Maximum Conductor Temperature 90°C (Current ratings are based on 30°C air temp. See technical section for de-rating factors).

Rated Voltage U_0/U 0.6/1kV.


Max AC Operating Voltage U_0 0.7kV.

Sheath Colour Yellow.

Standard Core Colours

4 Core – Red, White, Blue, Black.

Relevant Standards AS/NZS 5000.1, AS/NZS 3008, AS/NZS 1125, AS/NZS 3808, IEC 60332-1, **RoHS** Compliant.

Code	No. of Cores x Size (mm ²)	Approx. Stranding No. of wires x mm	Approx. Overall Diameter (mm)	Approx. Weight (Kg/Km)	Nominal Amps enclosed protected from sun @ 30°C fixed application Touching 	3 Phase Volt Drop @ 50Hz / MAX. Conductor Temp:	MAX Conductor Resistance @ 20°C	MAX Screened Resistance @ 20°C
						90°C (Mv/Am)	Ω /km	Ω /km
SMC04/6.0YEL	4 x 6.0	84/0.30	20.5	650	47	6.800	3.3	3.3
SMC04/16YEL	4 x 16.0	231/0.30	29.2	1407	89	2.550	1.21	1.21

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.