## **CURLY CORDS, AUTOROLLERS & CUSTOM INDUSTRIAL LEADS**

# **SML** SERIES

Heavy Duty Temporary Power Supply Leads

#### **APPLICATIONS:**

**Interconnection** of temporary power reticulation.

**Construction** site temporary power supply leads.

**Event** leads for power distribution on site.

Film Industry heavy duty leads providing safety on set.

#### **PRODUCT FEATURES:**

- ► Complete with Scame IP67, 415V plug and connector
- ► Tested and tagged for immediate use
- Yellow sheath for high visibility
- ► Tear, notch, pressure and water resistance
- ► Flame retardant
- Resistance to environmental factors like oxidation, ozone and sunlight
- ▶ Heat, oil and chemical resistant (See Technical Section)



#### **CONSTRUCTION:**

**Conductor** Annealed fine wires of plain copper stranded for high flexibility VDE 0295 (Class 5).

Insulation V-90HT.

Inner Sheath SER V-90HT.

**Screening** Flexible copper braid.

Sheath SER V-90HT.

Plug & Connector Scame IP67 - IEC 60309.

### **CHARACTERISTICS:**

Sheath Colour Yellow.

Relevant Standards AS/NZS 3012:2010, Appendix K.

Copper Braided Screen for maximum safety.

Code	Rating	Length (m)	Cores	mm²
SML3210	32 Amp	10	5	6
SML3215	32 Amp	15	5	6
SML3220	32 Amp	20	5	6
SML3230	32 Amp	30	5	6
SML6310	63 Amp	10	5	16
SML6315	63 Amp	15	5	16
SML6320	63 Amp	20	5	16
SML6330	63 Amp	30	5	16

Customised cable printing available - P.O.A

