

150 Series Conduit

150 Series Spiral Reinforced PVC



PRODUCT FEATURES

- ▶ All-insulated construction provides complete cable protection while the smooth bore facilitates fast and easy insertion
- ▶ Highly flexible, this series can be coiled on its own diameter without damage to the conduit or reduction in its cross section
- ▶ Corrosion free and free of jagged edges after cutting
- ▶ Weatherproof and self extinguishing to CEI 23-14 standard
- ▶ Temperature range 5°C to 70°C
- ▶ 30 metre reels

Code	Inner Diameter	Outer Diameter	Straight Connector	Gland Thread
150012	12mm	16mm	852012	16mm
150016	16mm	20mm	852016	20mm
150020	20mm	23mm	852020	25mm
150025	25mm	30mm	852025	32mm
150032	32mm	37mm	852032	40mm
150040	40mm	46mm	852040	50mm

150 Series Fittings



Code	Description	Thread	Rating
852012	Black PVC 12mm Straight Fitting	M16 x 1.5	IP65
852016	Black PVC 16mm Straight Fitting	M20 x 1.5	IP65
852020	Black PVC 20mm Straight Fitting	M25 x 1.5	IP65
852025	Black PVC 25mm Straight Fitting	M32 x 1.5	IP65
852032	Black PVC 32mm Straight Fitting	M40 x 1.5	IP65
852040	Black PVC 40mm Straight Fitting	M50 x 1.5	IP65

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.