

## Interlocked Switch Socket Outlets



### Interlocked Switch Socket Outlets

We have a comprehensive range of interlocked switch sockets with a mechanical interlocking system, high-performance isolator and modular option. From 16A to 125A offering a high quality product that is quick and easy to install and maintain.

### Flush and Surface Mounting Modular System

Ideally suited to installation needs in premises that require industrial sockets but where protrusion from the wall must be kept to a minimum, such as in kitchens, bars, public places, shops and business premises in general.

### Performances

- ▶ Range 500 - Interlocked switch IP44
- ▶ Range 505 - Interlocked switch IP67
- ▶ Range 568 - Interlocked switch, Internal DIN Rail to mount MCB or RCD, IP67
- ▶ Range 503 - Interlocked switch, GRP



16 & 32 Amp



16 & 32 Amp



63 Amp

### IP44 OMNIA Series

Code	Rating	Pins	Earth Position
<b>240v BLUE</b>			
<b>500.1683</b>	16 Amp	2 P + E	6H
<b>500.3283</b>	32 Amp	2 P + E	6H
<b>415v RED</b>			
<b>500.1686</b>	16 Amp	3 P + E	6H
<b>500.1687</b>	16 Amp	3 P + N + E	6H INDENT STOCK ITEM
<b>500.3286</b>	32 Amp	3 P + E	6H

### IP67 OMNIA Series

Code	Rating	Pins	Earth Position
<b>240v BLUE</b>			
<b>505.1683</b>	16 Amp	2 P + E	6H
<b>505.3283</b>	32 Amp	2 P + E	6H
<b>415v RED</b>			
<b>505.1686</b>	16 Amp	3 P + E	6H
<b>505.1687</b>	16 Amp	3 P + N + E	6H
<b>505.3286</b>	32 Amp	3 P + E	6H
<b>505.32864</b>	32 Amp	3 P + E	3H* (Reefer)
<b>505.3287</b>	32 Amp	3 P + N + E	6H
<b>505.6386</b>	63 Amp	3 P + E	6H
<b>505.6387</b>	63 Amp	3 P + N + E	6H

\*3H = Refrigerated Container

## Interlocked Switch Socket Outlets

Scame offers products suitable for installation into environments under potential risk of explosion. The Advance GRP series are made from glass reinforced polyester which guarantees excellent heat and fire resistance; it does not propagate flames, emit halogens or smoke.

### IP67 - Advance Series

Code	Rating	Pins	Earth Position
<b>415v RED</b>			
<b>568.3287</b>	32 Amp	3 P + N + E	6H + MCB/RCD Mount
<b>568.6386</b>	63 Amp	3 P + E	6H + MCB/RCD Mount
<b>568.6387</b>	63 Amp	3 P + N + E	6H + MCB/RCD Mount



568 Series

### 125A Switched Interlocked Socket Outlet

The glass reinforced polyester combined with the thickness of the casing walls guarantee excellent mechanical resistance to impacts (IK10). Offering resistance to chemical agents and atmospheric agents making it suitable for most extreme environmental conditions. The double degree of protection IP66 guarantees seal against entry of solid objects or liquid, also outstanding resistance to UV radiation.

Technical Specifications	
<b>Rated Current</b>	125A
<b>IP Rating</b>	IP66
<b>IK Rating</b>	IK10
<b>Rated Voltage</b>	100÷690V
<b>Operating Temperature</b>	-25°C ~ 60°C
<b>Self-extinguishing UL94</b>	V0
<b>Colour</b>	RAL 7037 grey

### IP66 - Advance (GRP) Series

<b>415v RED</b>				
<b>503.12586</b>	125 Amp	3 P + E	6H	
<b>503.12587</b>	125 Amp	3 P + N + E	6H	



503 Series

International Industrial Standard IEC60309-CEE17