

CONTROL CABLES

CTCY SERIES

Ultra Performance Flexible Rubber
CBS Control Cable 300/500V 80°C



APPLICATIONS:

Control and Signals For use on machines, portable tools, conveying equipment and other industrial applications requiring screened cables for EMC. These cables are flexible for fixed installation as well as occasional flexing without tensile load.

Harsh Environments With its UV stabilised, high flexibility, durable NBR sheath and excellent resistance to oil, heat, abrasion, ozone and solvents, this cable is suited to harsh industrial environments.

PRODUCT FEATURES:

- ▶ Extremely fine stranded copper conductor
- ▶ Prevents external interference
- ▶ UV stabilised
- ▶ Flame retardant
- ▶ Resistant to environmental factors like ozone
- ▶ Abrasion resistance
- ▶ Extreme flexibility with stranding to VDE 0295 Class 5 & 6
- ▶ To be earthed using EMC compatible glands
- ▶ Extensive heat, oil, solvent and chemical resistance (See *Technical Section*)

CONSTRUCTION:

Conductor Annealed plain copper stranded extreme flexibility (Class 5 & 6).

Insulation SPVC V-75.

Screening Tinned copper braid 85% minimum coverage.

Inner Sheath SER 90.

Sheath SER 90.

CHARACTERISTICS:

Operating Temperature Range Fixed -20 to 80°C / Flexing -5 to 80°C.

Maximum Conductor Temperature 80°C (Current ratings are based on 30°C air temp. See technical section for de-rating factors).

Rated Voltage U_o/U 300/500v.v

Max AC Operating Voltage U_o 318v.

Minimum Bending Radius Fixed 7.5 x cable diameter / Flexing 15 x cable diameter.

Sheath Colour Black.

Standard Core Colours White (numbered) plus 1 Green/Yellow Earth.

Relevant Standards IEC 60332-1, AS/NZS 1125, AS/NZS 3808, **RoHS** Compliant.

Code	No. of Cores x Size (mm ²)	Approx. Stranding No. of wires x mm	Approx. Overall Diameter (mm)	Approx. Weight (Kg/Km)
CTCY03/0.75	3 x 0.75	24/0.20	9.1	131
CTCY07/0.75	7 x 0.75	24/0.20	11.5	201
CTCY12/0.75	12 x 0.75	24/0.20	14.8	335
CTCY18/0.75	18 x 0.75	24/0.20	15.6	420
CTCY02/1.5	2 x 1.5	48/0.20	10.2	168
CTCY07/1.5	7 x 1.5	48/0.20	13.9	323
CTCY12/1.5	12 x 1.5	48/0.20	16.8	521
CTCY19/1.5	19 x 1.5	48/0.20	20.7	705
CTCY07/2.5	7 x 2.5	80/0.20	16.5	374

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.