

## FT655-ESCS SERIES

High Performance Multipair Overall & Individually Foil Screened Tinned Instrumentation Cable 0.6 / 1kV 90°C



### APPLICATIONS:

**Signal and Controls** Power control or signal/instrumentation cables on machines, conveying equipment or similar industrial applications.

**Marine** Tinned copper conductors for use in marine applications.

**Low Voltage** With its 600V rated insulation and 1.8mm thick sheath, this series is suitable to run next to low voltage mains.

### PRODUCT FEATURES:

- ▶ Extremely pliable PVC sheath
- ▶ UV stabilised
- ▶ Flame retardant
- ▶ Reduced flame propagation
- ▶ Heat, oil and chemical resistant *(See Technical Section)*

### CONSTRUCTION:

**Conductor** Annealed tinned copper stranded (Class 2).

**Insulation** Special SPVC V-90 (available in LSHF on request).

**Filler** Non-hydroscopic polypropylene filler.

**Screening** Collective shield of aluminium/polyester foil complete with Tinned copper drain wire.

**Sheath** Special SPVC 5V-90 (available in LSHF on request).

### CHARACTERISTICS:

**Operating Temperature Range Fixed** -20°C to 90°C.

**Maximum Conductor Temperature** 90°C.

**Rated Voltage** 0.6/1kV.

**Minimum Bending Radius** 10 x cable diameter.

**Sheath Colour** Black.

**Standard Core Colours** Each pair – 1 x White and 1 x Black conductor, with numbered cores.

**Relevant Standards** AS/NZS 1125, AS/NZS 3808, IEC 60332-1-2, IEC 60079.14, IEC 60332-3-22, **RoHS** Compliant.

Property	1.5mm <sup>2</sup>	
	Value	Units
DC Conductor Resistance @ 20°C	13.6	Ω/km
Inductance @ 1kHz	0.95	mH/km
L/R ratio @ 1kHz	36.5	μH/Ω
Insulation Resistance @ 20°C	140	MΩ.km

Code	No. of Cores x Size (mm <sup>2</sup> )	Nearest AWG	Approx. Stranding No. of wires x mm <sup>2</sup>	Approx. Overall Diameter (mm)	Approx. Weight (Kg/Km)
<b>FT65102ES</b>	1 pair 1.5	15	7/0.50	10.0	63
<b>FT65502ESCS</b>	2 pair 1.5	15	7/0.50	15.2	123
<b>FT65504ESCS</b>	4 pair 1.5	15	7/0.50	17.6	209
<b>FT65103ES</b>	1 triple 1.5	15	7/0.50	10.4	80

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.