

# SCAME PLUGS, CONNECTORS & ENCLOSURES

## Switches & Accessories



### Rectangular Bulkhead Light - IP55

- ▶ For incandescent lamps
  - ▶ Mizar series
  - ▶ Max 60W
  - ▶ Lampholder E27 (screw bulb)
- Code: 786.2761** Indent Stock Item



Blank Plate for Panel Cutouts  
**Code: 654.0100**



Blank Plate for 4 Din Modules  
**Code: 654.0400**

#### Technical Specifications

<b>IP Rating</b>	IP55
<b>Operating Temperature</b>	Polycarbonate diffuser: -15°C~35°C
<b>Glow Wire Test</b>	650°C
<b>Material</b>	Engineering Plastic
<b>IK Rating</b>	IK04~IK07
<b>Double Insulation</b>	Yes
<b>Colour of Diffuser</b>	Red



Blank Plate for Panel Cutouts  
▶ IP55  
**Code: 654.0120**

### Data Communications Enclosure

- ▶ IP66 rated enclosure even with cables connected.
- ▶ Tinted polycarbonate cover to see inside.
- ▶ Polycarbonate enclosure - shockproof, chemical and UV resistant.
- ▶ Accepts PDL 600 series mechanisms including: RJ45, CAT5, CAT6 (with/ without POE) F-type TV, RCA, HDMI, BT Telephone.
- ▶ Ideal for external connections - phone, data cable, speakers, industrial access points and wash down areas.
- ▶ Flush wall mounting kit available (**Code: 137.121**)



**Code: 137.COMM**

#### Technical Specifications

	EN60670-1
<b>IP Rating</b>	IP66
<b>Operating Temperature</b>	-5°C to 60°C
<b>Material</b>	Polycarbonate
<b>IK Rating</b>	IK07
<b>Cable Inserts</b>	M20
<b>Colour</b>	BASE: RAL7035 grey/ LID: smoke tinted transparent



4 DIN Terminal  
**Code: 654.0365**



8 DIN Terminal  
**Code: 654.0363**



12 DIN Terminal  
**Code: 654.0361**

## Domestic Outlets

### Watertight Cover

- ▶ 10A or 15A single outlet - IP55



Code	Rating	Pins
<b>570.5052A-10</b>	10 Amp	2P+E
<b>570.5052A-15</b>	15 Amp	2P+E

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.

