

FDCY SERIES

High Performance Flexible VSD Power Cable 0.6/1kV 80°C



APPLICATIONS:

VSD Connection Designed for the connection of AC Variable Speed Drives (VSD) or where a flexible EMC screened cable is required. These cables are flexible for fixed installation as well as occasional flexing without tensile load.

PRODUCT FEATURES:


- ▶ Helps avoid reactance with other devices outside the plant
- ▶ UV stabilised
- ▶ Flame retardant
- ▶ Moisture resistant
- ▶ Resistant to environmental factors such as oxidation, ozone and sunlight
- ▶ To be earthed using an EMC compatible gland
- ▶ Heat, oil and chemical resistant (*See Technical Section*)

CONSTRUCTION:

Conductor Annealed plain copper stranded high flexibility (Class 5).
Insulation PVC.
Screening 85% tinned copper braid screen.
Sheath SPVC.

CHARACTERISTICS:

Operating Temperature Range Fixed -40°C to 80°C / Flexing -15°C to 70°C.
Maximum Conductor Temperature 80°C (Current ratings are based on 30°C air temp. See technical section for de-rating factors).
Rated Voltage U_o/U 0.6/1kV.
Max AC Operating Voltage U_o 0.7kV.
Minimum Bending Radius Fixed 6 x cable diameter / Flexing 15 x cable diameter.
Sheath Colour Black.
Standard Core Colours Black (Numbered) Plus / Green/Yellow Earth.
Relevant Standards IEC60228, EN50525-2-51, IEC 60332-1,
RoHS Compliant, Conform to 2014/35/E4CE

Code	No. of Cores x Size	Approx. Stranding Power	Approx. Overall Diameter	Approx. Weight	Nominal Amps	3 Phase Volt Drop
		No. of wires x mm	(mm)	(Kg/Km)	un-enclosed protected from sun @ 30°C fixed application	@ 50Hz / MAX. Conductor Temp:
					Fixed Installation Touching 	80°C (Mv/Am)
FDCY5/2.5	5 x 2.5	50/0.25	15	457	20	16.400
FDCY5/4.0	5 x 4.0	56/0.30	17.3	661	25	10.200

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.