

SCAME PLUGS, CONNECTORS & ENCLOSURES

Domino System Modular Enclosures IP66

All dimensions are:
H x W x D



Consumer Units

Units come with or without busbar. Use **W** to include busbar.

2 DIN Consumer Units

135 x 76 x 102mm

672.2002



4 DIN Consumer Units

190 x 112 x 106mm

672.2004

672.2004W



8 DIN Consumer Units

190 x 184 x 106mm

672.2008

672.2008W



12 DIN Consumer Units

250 x 256 x 140mm

672.2012

672.2012W



16 DIN Consumer Units

250 x 328 x 140mm

672.2016

672.2016W



24 DIN Consumer Units

400 x 256 x 140mm

672.4024

672.4024W



32 DIN Consumer Units

400 x 328 x 140mm

672.4032

672.4032W



48 DIN Consumer Units

550 x 328 x 140mm

672.5048



48 DIN

64 DIN Consumer Units

700 x 328 x 140mm

672.7064 Indent Stock Item



64 DIN

Enclosures with Plain Front Panel

8 DIN

w/ Plain Front Panel

340 x 184 x 106mm

672.2100



16 DIN

w/ Plain Front Panel

400 x 328 x 140mm

672.4116



16 DIN

w/ Plain Front Panel

550 x 328 x 140mm

672.5116



Enclosures with IEC309 Series cut out

8 DIN

w/ IEC309 Series cut out

340 x 184 x 106mm

Outlets: 10, 16 and 32 Amp

672.2300



12 DIN

w/ IEC309 Series cut out

400 x 256 x 140mm

Outlets: 10, 16 and 32 Amp

672.3300



16 DIN

w/ IEC309 Series cut out

400 x 328 x 140mm

Outlets: 10, 16 and 32 Amp

672.4316 Indent Stock Item



16 DIN

w/ IEC309 Series cut out

Size: 550 x 328 x 140mm

Outlets: 10, 16 and 32 Amp

672.5616



Hose proof rating makes them eminently suitable for food industry applications and for harsh environments.

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.