

## SCAME Plugs



Socket Front View



### IP67 OPTIMA Plug

Code	Rating	Pins	Earth Position
<b>110v YELLOW</b>			
<b>218.1630</b>	16 Amp	2 P + E	4H
<b>240v BLUE</b>			
<b>218.1633PTR</b>	16 Amp	2 P + E	6H Ins. Perforation
<b>218.1633TR</b>	16 Amp	2 P + E	6H
<b>226.1633</b>	16 Amp	2 P + E	6H (Right Angle)
<b>218.3233</b>	32 Amp	2 P + E	6H
<b>218.6333</b>	63 Amp	2 P + E	6H
<b>415v RED</b>			
<b>218.1636P</b>	16 Amp	3 P + E	6H Ins. Perforation
<b>218.1637P</b>	16 Amp	3 P + N + E	6H Ins. Perforation
<b>218.3236</b>	32 Amp	3 P + E	6H
<b>218.32364</b>	32 Amp	3 P + E	3H* (Reefer)
<b>218.3237</b>	32 Amp	3 P + N + E	6H
<b>218.6336</b>	63 Amp	3 P + E	6H
<b>218.6337</b>	63 Amp	3 P + N + E	6H
<b>218.12536</b>	125 Amp	3 P + E	6H
<b>218.12537</b>	125 Amp	3 P + N + E	6H

\* 3H = Refrigerated Container

Fittings 63 Amp and above have Pilot Pin and are IP67 Rated

### IP44 OPTIMA Plug

Code	Rating	Pins	Earth Position
<b>240v BLUE</b>			
<b>213.1633PTR</b>	16 Amp	2 P + E	6H Ins. Perforation
<b>213.1633TR</b>	16 Amp	2 P + E	6H
<b>213.3233</b>	32 Amp	2 P + E	6H
<b>415v RED</b>			
<b>213.1636P</b>	16 Amp	3 P + E	6H Ins. Perforation
<b>213.1638</b>	16 Amp	2 P + E	9H
<b>213.3236</b>	32 Amp	3 P + E	6H
<b>213.3237</b>	32 Amp	3 P + N + E	6H



### IP44 Angled Plug

Code	Rating	Pins	Earth Position
<b>221.1633</b>	16 Amp	2 P + E	6H

International Industrial Standard IEC60309-CEE17

### Wiring and Installation

Rated Voltage	WIRING CAPACITY OF TERMINALS (mm <sup>2</sup> )					MAX. CABLE SIZE ACCEPTED BY CABLE CLAMP		
	Rated Voltage (A)	Plugs, Connectors and Appliance Inlets		Socket Outlets		Rated Current (A)	Outside $\phi$ mm	
		Min	Max	Min	Max		Min	Max
Over 50V	16A	1	2.5	1.5	4	16A	8	15
	32A	2.5	6	2.5	10	32A	11.5	21
	63A	6	16	6	25	63A	17	31
	125A	16	50	25	70	125A	26	48

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.