## SCAME PLUGS, CONNECTORS & ENCLOSURES

# Switches & Accessories

#### Rectangular Bulkhead Light

- IP55
- ► For incandescent lamps
- ▶ Mizar series
- ► Max 60W
- ► Lampholder E27 (screw bulb)

Code: 786.2761 Indent Stock Item



Technical Specifications	
IP Rating	IP55
Operating Temperature	Polycarbonate diffuser: -15°C~35°C
<b>Glow Wire Test</b>	650°C
Material	Engineering Plastic
IK Rating	IK04 <sup>~</sup> IK07
<b>Double Insulation</b>	Yes

Red

#### **Data Communications Enclosure**

▶ IP66 rated enclosure even with cables connected.

**Colour of Diffuser** 

- ► Tinted polycarbonate cover to see inside.
- ► Polycarbonate enclosure shockproof, chemical and UV resistant.
- Accepts PDL 600 series mechanisms including: RJ45, CAT5, CAT6 (with/ without POE) F-type TV, RCA, HDMI, BT Telephone.
- ▶ Ideal for external connections phone, data cable, speakers, industrial access points and wash down areas.
- Flush wall mounting kit available (Code: 137.121)

Code: 137.COMM

Technical Specifications			
	EN60670-1		
IP Rating	IP66		
Operating Temperature	-5°C to 60°C		
Material	Polycarbonate		
IK Rating	IK07		
Cable Inserts	M20		
Colour	BASE: RAL7035 grey/ LID: smoke tinted transparent		





Blank Plate for **Panel Cutouts** 





Blank Plate for 4 Din Modules Code: 654.0400



**Blank Plate for Panel Cutouts** 

▶ IP55

Code: 654.0120







4 DIN Terminal Code: 654.0365

8 DIN Terminal Code: 654.0363

12 DIN Terminal Code: 654.0361

### **Domestic Outlets**

#### Watertight Cover

▶ 10A or 15A single outlet - IP55



Code	Rating	Pins
570.5052A-10	10 Amp	2P+E
570.5052A-15	15 Amp	2P+E

