

# NICKEL COATED BRASS ADAPTORS

## (NO THREADING REQUIRED)

**BS standard pitch thread 1.5mm.** A no-threading alternative for installing galvanised steel conduit. A new alternative way to install galvanised steel conduit with no threading! Install galvanised steel conduit faster with the new adaptors from Firstflex cables. Reduction in tooling and threading time. Tested and approved to AS/NZS 2053:7

### INSTRUCTIONS:

1. Cut conduit to required length.
2. Wipe surfaces to be joined.
3. Apply recommended MTA001 adhesive to the outer surface of the conduit (Permabond A1046 / Loctite 510/638 or equivalent).
4. Adaptors may be pressed onto the conduit by hand, or tapped on. Ensure that the conduit passes the dimple – this maintains a constant earth.
5. Job complete!

## GCMTA

Male Thread to Female Plain Metal Adaptor



Code	Size
<b>GCMTA 20</b>	20mm
<b>GCMTA 25</b>	25mm
<b>GCMTA 32</b>	32mm
<b>GCMTA 40</b>	40mm
<b>GCMTA 50</b>	50mm

## GCMTA 001

Adhesive

Code	Size
<b>GCMTA 001 ADHESIVE</b>	50ml, 100 Joints



## GCFTA

Female Thread to Female Plain Metal Adaptor



Code	Size
<b>GCFTA 20</b>	20mm
<b>GCFTA 25</b>	25mm
<b>GCFTA 32</b>	32mm
<b>GCFTA 40</b>	40mm

## GCFPC

Female Plain to Female Plain Metal Adaptor



Code	Size
<b>GCFPC 20</b>	20mm
<b>GCFPC 25</b>	25mm
<b>GCFPC 32</b>	32mm
<b>GCFPC 40</b>	40mm
<b>GCFPC 50</b>	50mm

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.