

MAXCAB CONSTRUCTION CABLES & BUILDING WIRE

VIN SERIES

Standard Performance Fixed Circular
TPS Cable 0.6/1kV 75°C



APPLICATIONS:

- Power** Suitable for main and submains in a fixed location.
- Enclosures** Internal wiring inside and between switchboards.
- Buildings** Suitable for interconnection of mains between floors. Typical use within Network authority works.

PRODUCT FEATURES:




- ▶ Flame retardant
- ▶ UV stabilised
- ▶ Metre marked for better length control
- ▶ Oil and chemical resistant (See Technical Section)

CONSTRUCTION:

- Conductor** Annealed plain copper stranded (Class 2)
- Insulation** V-75
- Sheath** SPVC

CHARACTERISTICS:

- Operating Temperature range** -20°C to 75°C
- Maximum Conductor Temperature** 75°C (Current ratings are based on 30°C air temp. See technical section for de-rating factors).
- Rated Voltage** U_o/U 0.6/1kV
- Minimum Bending Radius** Fixed - 12 x cable diameter
- Insulation Core Colour** White
- Sheath Colour**
(Use colour letters at the end of the code when ordering)
BK - Black
BL - Blue
RD - Red
WH - White
- Relevant Standards** AS/NZS 5000.1, AS/NZS 3808, AS/NZS 3008, AS/NZS 1125, **RoHS** Compliant

Code	No. of Cores x Size (mm ²)	Approx. Stranding no. of Wires x mm	Approx. Overall Diameter (H x W) (mm x mm)	Approx. Weight (Kg/Km)	Nominal Amps @ 30°C Fixed Installation - Three Phase			Three Phase Volt Drop 75°C (mV/Am)
					Touching 	Enclosed wiring enclosure in Air 	Partially surrounded by thermal insulation 	
VIN016	1 x 16	7/1.70	9.9	230	82	71	44	2.55
VIN025	1 x 25	7/2.14	11.6	340	111	92	57	1.65
VIN035	1 x 35	19/1.53	12.9	440	136	114	71	1.18
VIN070	1 x 70	19/2.14	16.3	800	210	173	107	0.591

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.