

## CURLY CORDS, AUTOROLLERS & INDUSTRIAL POWER PRODUCTS

CC Series	178
Cordset	179
SCAME Cable Autoroller	179



## **CURLY CORDS, AUTOROLLERS & INDUSTRIAL POWER PRODUCTS**

# 

Extreme Performance Industrial Curly Cord Spiral Cables PUR Outer Sheath 1:4 Elasticity Ratio

#### **APPLICATIONS:**

**Mobile Tools** Due to its long elastic memory and cable life, this cable is suitable for connection of mobile power tools in production lines, engineering and mechanical workshops and laboratory environments.

**Food & Beverage** With its microbe and hydrolysis resistant and super durable PUR sheath, this cable suits the food and beverage industry.

#### **PRODUCT FEATURES:**

- Extreme abrasion resistance
- Excellent elasticity and reverse bending strength
- UV stabilised
- ► Flame retardant
- Resistance to microbes
- Supplied with 200mm tails
- Oil and chemical resistant (See Technical Section)



#### CONSTRUCTION:

Conductor Annealed plain copper stranded high flexibility (Class 5).Insulation EPR rubber.Sheath Orange halogen free PUR polyurethane TMPU (HD22.1 S2).

#### CHARACTERISTICS:

Operating Temperature Range Flexing -25°C to 90°C Rated Voltage 0.75mm² to 1.0mm² - Uo/U 300/500V / 1.5mm² - Uo/U 0.6/1kV. Standard Core Colours 3 core – Blue, Brown, Green/Yellow. 4 core – Blue, Brown, Black, Green/Yellow. 5 core – Blue, Brown, Black, Grey, Green/Yellow. Relevant Standards IEC 60228, IEC 60332-1, C € Directive 2006/95/EC, *ROHS* Compliant.

Code	Cores	mm²	Length Compressed (m)	Length Extended (m)
CCEPR25	3	1.5	0.5	2.0
CCEPR26	3	1.5	1.0	4.0
CCEPR27	3	1.5	1.5	6.0
CCEPR66	3	1.5	3.5	14.0
CCEPR29	3	2.5	1.0	4.0
CCEPR31	4	0.75	0.5	2.0
CCEPR32	4	0.75	1.0	4.0
CCEPR46	4	1.5	1.0	4.0
CCEPR47	4	1.5	1.5	6.0
CCEPR56	5	1.5	1.5	6.0

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.



## **CURLY CORDS, AUTOROLLERS & INDUSTRIAL POWER PRODUCTS**

# Cordset

3 Pin Moulded male plug & 75mm Stripped Tails 250/440V V-90

#### **APPLICATIONS:**

**Power** Replacement cord for power tools, construction and engineering equipment.

#### **PRODUCT FEATURES:**

- Annealed plain copper stranded high flexibility (Class 5)
- UV Stabilised
- Oil & Chemical Resistant



CORD3MOR

3 Metres

## **SCAME Cable Autoroller**

# Autoroller - Cable reel with automatic rewind and connector

#### **APPLICATIONS:**

Made of an impact-resistant engineering plastic, it features high mechanical strength and a patented device which assures quick and safe rewinding. Suitable for connections subject to medium level mechanical stresses in industrial workshops, farms (such as portable lamps, electric tools, motors etc).

#### **PRODUCT FEATURES:**

- Automatic cable dispense and rewind
- Includes wall mounting bracket designed to swivel
- IP44 240v 16 Amp 2 P + E connector
- Keeps workshop tidy
- Meets OSH workshop safety standards




#### Autoroller - 15 metre lead

Complete with cable. 15m x 3 core 1.5mm<sup>2</sup> cable

Code: 751.40315-15C

Firstlex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstlex reserves the right to modify specifications at any time.





179

# Industrial Grades

## Pre-made Industrial and Marine Leads

FIRSTFLEX

- Firstflex HD Series Heavy Duty and MLG2
- Available in 10, 15, 20 & 30m Length
- Scame IEC and PDL plug options available
- I6 or 32 Amp (63 and 125 Amp available on request)
- IP66/67 Plugs and Connectors
- Tested and tagged for immediate use
- Tear, notch, pressure and water resistance
- UV Stabilised
- Custom lead configurations available on request
- Enquire about custom printing

