

FT75-CS SERIES

High Performance Multipair Overall Foil Screened Tinned Instrumentation Cable
110VAC 90°C



APPLICATIONS:

Signal and Controls Power control or signal/instrumentation cables on machines, conveying equipment or similar industrial applications.

Marine Tinned copper conductors for use in marine applications

Oil and gas industry with vertical flame propagation to IEC 60332-3-22.

PRODUCT FEATURES:

- ▶ Tinned copper conductors
- ▶ Extremely pliable PVC sheath
- ▶ UV stabilised
- ▶ Flame retardant
- ▶ Reduced flame propagation
- ▶ Heat, oil and chemical resistant (See Technical Section)

CONSTRUCTION:

Conductor Annealed tinned copper stranded (Class 2).

Insulation Special SPVC V-90 (available in LSHF on request).

Filler Non-hydroscopic polypropylene filler.

Screening Collective shield of aluminium/polyester foil complete with tinned copper drain wire (7 strands of 0.2mm²).

Sheath Special SPVC 5V-90 (available in LSHF on request).

CHARACTERISTICS:

Operating Temperature Range Fixed -20°C to 90°C.

Maximum Conductor Temperature 90°C.

Rated Voltage 110VAC / 150VDC.

Minimum Bending Radius 10 x cable diameter.

Sheath Colour Black.

Standard Core Colours Each pair – 1 x White and 1 x Black conductor, with numbered cores.

Relevant Standards AS/NZS 1125, AS/NZS 3808, IEC 60332-1-2, IEC 60332-3-22, IEC 60079.14, **RoHS** Compliant.

Property	0.75mm ²	
	Value	Units
DC Conductor Resistance @ 20°C	24.8	Ω/km
Inductance @ 1kHz	0.98	mH/km
L/R ratio @ 1kHz	20	μH/Ω
Insulation Resistance @ 20°C	140	MΩ.km

Code	No. of Cores x Size (mm ²)	Nearest AWG	Approx. Stranding No. of wires x mm ²	Approx. Overall Diameter (mm)	Approx. Weight (Kg/Km)
FT7501CS	1 pair 0.75	18	7/0.37	5.8	40
FT7502CS	2 pair 0.75	18	7/0.37	8.5	71
FT7504CS	4 pair 0.75	18	7/0.37	10.0	118