

CONDUIT ADAPTORS (NO THREADING REQUIRED)

BS standard pitch thread 1.5mm. A no-threading alternative for installing galvanised steel conduit. A new alternative way to install galvanised steel conduit with no threading! Install galvanised steel conduit faster with the new adaptors from Firstflex cables. Reduction in tooling and threading time. Tested and approved to AS/NZS 2053:7

INSTRUCTIONS:

1. Cut conduit to required length.
2. Wipe surfaces to be joined.
3. Apply recommended MTA001 adhesive to the outer surface of the conduit (Permabond A1046 / Loctite 510/638 or equivalent).
4. Adaptors may be pressed onto the conduit by hand, or tapped on. Ensure that the conduit passes the dimple – this maintains a constant earth.
5. Job complete!

GCMTA

Male Thread to Female Plain
Metal Adaptor



Code	Size
GCMTA 20	20mm
GCMTA 25	25mm
GCMTA 32	32mm
GCMTA 40	40mm
GCMTA 50	50mm

GCMTA 001

Adhesive

Code	Size
GCMTA 001 ADHESIVE	50ml, 100 Joints



GCFTA

Female Thread to Female Plain
Metal Adaptor



Code	Size
GCFTA 20	20mm
GCFTA 25	25mm
GCFTA 32	32mm
GCFTA 40	40mm

GCFPC

Female Plain to Female Plain
Metal Adaptor



Code	Size
GCFPC 20	20mm
GCFPC 25	25mm
GCFPC 32	32mm
GCFPC 40	40mm
GCFPC 50	50mm

Firstflex has taken every precaution to ensure accurate information in this catalogue, but accept no liability for any errors or omissions. Firstflex reserves the right to modify specifications at any time.